

Classic

Model 2020ASZ-X4 All Terrain



Cruise Car, Inc.
P: 941.929.1630
www.cruiseincar.com

Descriptions:	Utility Cart
GENERAL SPECIFICATIONS	
Passenger Capacity	4
Voltage (V)	48V
Range (loaded)	46.6 miles
Max. Speed (m/h)	19.88
Max. Climbing Ability (loaded)	28%
Overall Dimensions (LxWxH) (ft)	8.20 x 3.94 x 6.23
Max. Loading Weight (lbs)	838 lbs
Net Weight (lbs)	1058 lbs
CONTAINER QUANTITY	
If carts are ordered with the top basket and front basket and the bumper	
Qty/40'	12 pcs
Qty/40'HQ	18 pcs
If carts are ordered without the top basket and front basket and the bumper	
Qty/40'	14 pcs
Qty/40'HQ	20 pcs



CONFIGURATIONS ("S" stands for Standard Configuration and "O" stands for Optional Configuration)		
DESCRIPTIONS:	REMARKS:	
Body	Steel framework + injected plastic	S
Body color (front body and rear body)	Camouflaged Solid color	S O
Roof	Fiberlass	S
Roof color	Solid color	S
Windshield	one-piece see-through Foldable	S O
Seats: 1) Backrest and Cushion 2) Armrest 3) Rear foldable seat	Sponge + artificial leather Plastic Aluminum rear board	S S S
Floor Protective side	Non-slipping plastic Stainles steel	S S
Front bumper	Steel	O
Front basket	\	O
Top basket	\	O
Lighting system and horn	Front headlights, ? taillights(combined brake lights with reverse lights), with DC-DC converter (converting from 48V to 12V) and horn	S
Dashboard	Injected plastic 1 battery charging meter,combined switch, key ignition, forward/reverse switch, horn switch	S S
Battery	Trojan battery T605 X 8pcs	S
Motor (hp)	5.5	S
Controller	Curtis brand 1268	S
Steering system	Single-stage rack and pinion steering system, automatic rocker compensating function	S
Brake System	mechanical brake + parking brake system	S
Accelerator	Stepless speed change	S
Suspension System	Integrative front axle, leaf spring+vibration absorber	S
Driving Mode	Rear axle two stage deceleration, motor direct driving	S
Rear axle	Integrative rear axle, leaf spring + vibration absorber	S
Wheel and tire	25 x 10-12 tire, 12*7 Steel wheel 22 x 10-10 tire, 10*8 Steel wheel	S O
Seat belt	2-point	O

Hand bar	\	S
Rear view mirror	External	S
ACCESSORIES		
Charger	China origin, input 110V-240V~50Hz-60Hz, output 48V, 25A	S
Solar	\	O