

Classic

Model 2028KSZ-X4



Cruise Car, Inc.
P: 941.929.1630
www.cruiseincar.com

Descriptions:	Personal Carrier (Passenger Car)
GENERAL SPECIFICATIONS	
Passenger Capacity	4
Range (loaded)	46.6 miles
Max. Speed (m/h)	19.88
Minimum turning radius (ft)	9.84
Max. Climbing Ability (loaded)	20%
Max. movement after brake	≤13.12
Overall Dimensions (LxWxH) (ft)	7.68 x 3.87 x 5.74
Max. Loading Weight (lbs)	881 lbs
Net Weight (lbs)	1058 lbs
Qty/20'	6 units
Qty/40'	14 units
Qty/40'HQ	22 units



CONFIGURATIONS ("S" stands for Standard Configuration and "O" stands for Optional Configuration)		
DESCRIPTIONS:	REMARKS:	
Body	Steel framework + plastic body	S
Roof	Fiberlass	S
Windshield	One-piece Organic glass	S
Stainless steel package	Including front upright, rear upright, sweater basket	O
2point seat belt	\	O
Windshield, hinged	\	O
Large seats: 1) Backrest and Cushion 2) Armrest 3) Plastic seat bottom	Rebond seat + artificial leather	S
	Formed	S
	\	S
Backrest in wood finish	\	O
Floor	Rubber	S
Golf bag holder	\	S
Dashboard in black plastic finish	Forward/reverse switch, battery capacity indicator, ignition key	S
Dashboard in wood finish	Wood finish	O
Steering wheel in wood finish	\	O
Beverage holders	4 cups drink holders	S
Lighting system and horn	2 headlights, 2 front turn signals, 2 taillights(each combined 1 brake light with 1 turn signal), with DC-DC converter (converting from 48V to 12V), horn	S
Glove box	\	S
Side trim, plastic	Stainless steel	S
Score card holder	On steering wheel	S
Towing bracket	On front of golf car	S
Battery	Trojan battery T605 X 8 pcs	S
	Trojan battery T875 X 6 pcs	O
Battery tray	To protect the battery liquid touching the frame	S
Motor (hp)	5.5	S
	4.02	O
Controller	Curtis brand 1268	S
12V accessory plug	To be mounted on the dashboard	O
Hour meter	\	O
Steering system	Single-stage rack and pinion steering system, automatic rocker compensating function	S
Brake system	Mechanical brake	S
	4-wheel hydraulic brake + hand brake	O
Accelerator	Stepless speed change	S
Suspension system	Front and rear plate spring + vibration absorber	S
Driving mode	Rear axle two stage deceleration, motor direct driving	S

Rear axle	Gear ratio12.49:1 Gear ratio10.25:1 (New gear ratio, working together with 48V/4KW motor to get high speed of 40km/h or 25mp)	S O
Tire	205/50-10 4PR 18*8.5-8 4PR	S O
Wheel in 10"	10*7 Alumimum wheel 6J-10 Steel wheel, wheel cover 8*7 Steel Wheel, wheel cover	O S S
Reversing alarm	\	S
Side rear view mirror	Two pieces per cart	O
Two points seat belt	Four pieces per cart	O
Wheel cap for 10" wheel	\	S
Cooler	\	O
Enclosure	\	O
ACCESSORIES		
Charger	China origin, input 110V-240V~50Hz-60Hz, output 48V, 25A Imported on-board charger	S O
Solar	\	O