

Utility Vehicle

Model 6060J-X2



Cruise Car, Inc.
P: 941.929.1630
www.cruiseincar.com

Descriptions:	Lift Truck
GENERAL SPECIFICATIONS	
Passenger Capacity	2
Range (loaded)	49 miles
Max. Speed (m/h)	18.64
Minimum turning radius (ft)	9.51 ft
Max. Climbing Ability (loaded)	20%
max. loading capacity (lbs)	661.39 lbs
max. lifting height (m)	19.69 ft
Overall Dimensions (LxWxH) (mm)	11.40 x 4.56 x 7.05
Truck motor (hp)	4.02
Lifter motor (hp)	1.98
Battery quantity (pcs)	8
Voltage of each battery (V)	6
battery capacity (AH)	180
Qty/40'	3



Notes: all above offers are based on full container order quantity. 2% free parts will be provided with each shipment.

CONFIGURATIONS ("S" stands for Standard Configuration and "O" stands for Optional Configuration)

DESCRIPTIONS:	REMARKS:	
Body	Steel framework + Steel plate body	S
Seats: 1) Backrest and Cushion	Sponge + artificial leather	S
2) Armrest	Stell pipe	S
Floor	Bamboo board+ plastic	S
Side rear view mirror	One piece each side	O
Cover for rear bed	Plywood	S
Battery	Trojan battery T605, 8 pcs	O
Motor (hp)	4.02	s
Controller	Curtis brand	S
Lights	Front: 2 Headlights, 2 front turn signals; Back: 2 rear turn signals, 2 brake lights	S
Dashboard	Voltmeter, ammeter, speedometer, turn signal indicator, headlight indicator, emergency switch, ignition key; Headlight switch, turn signal switch, horn button	S
DC/DC Converter	48V/12V DC/DC	S
Horn and reverse alarm	\	S
Cup drinker holder	1 ps	S
Steering system	Rack and pinion steering system	S
Brake system	Front and rear drum pneumatic brake system	S
Front end and Suspension system	Independent suspension, cylinder pneumatic vibration absorber	S
Rear end and suspension system	Integrated rear end, steel plate spring suspension, cylinder pneumatic vibration absorber	S
Transmission system	Clutch, 4F+1R gear box, transmission shaft	S
Tire	145/80-R12	S
Seat belt	2 point seat belt	O
Front Canvas roof with windshield	\	O
Hub cover	\	S
ACCESSORIES		
Charger	China origin, input 110V-240V~50Hz-60Hz, output 48V, 25A	S