

Kudo

Model 6062K-X6



Cruise Car, Inc.
P: 941.929.1630
www.cruiseincar.com

Descriptions:	Personal Carrier (Passenger Car)	
GENERAL SPECIFICATIONS	6062K (Sepex System)	6062K01 (Sepex System)
Battery	T605X 8 PCS	T605X 8 PCS
Motor (hp)	5.5	4.02
Controller	Curtis 1268	Curtis 1266
Passenger capacity	6	
Voltage (V)	48V	
Range (loaded)	49.71 miles	
Max. speed (m/h)	24.85 (normally it is set at 20.51 if you have no special request for 24.85)	
Minimum turning radius (ft)	13.12	
Max. climbing ability (loaded)	0.28	
Max. movement after brake	≤13.12	
Overall dimensions	12.01 x 4.59 x 5.94	
Max. loading weight	992 lbs	
Net weight	1764 lbs	
Qty/40'	3	
Qty/40'HQ	6	



CONFIGURATIONS ("S" stands for Standard Configuration and "O" stands for Optional Configuration)		
DESCRIPTIONS:	REMARKS:	
Body	Steel framework + fiberglass body	S
Roof	Aluminum frame + fiberglass	S
Windshield	Toughened glass	S
Seats: 1) Backrest and Cushion 2) Armrest	Sponge + artificial leather Soft expanded plastic	S S
Seat Belt (3-point)	6 pcs per cart	O
Hand Holder for Front Passenger	1 pc hand holder fixed under the roof	S
Hand holder for rear passenger	2pcs, fixed on front backrest	S
Storage net	1pc each on backrest	S
Inner rear view mirror	1 pc	S
Side Rear View Mirror	2 pcs per cart	S
Floor	Bamboo + artificial leather	S
Dashboard	Forward/reverse switch, headlight indicator, turn signal indicator, ignition key, battery state indicator, ammeter, emergency switch; turn signal switch, headlight switch, windscreen wiper switch, horn button; Storage for miscellaneous items, Radio and tape player	S
Radio and tape player	\	S
If with CD player	Replacing original Radio & Tape player	O
Microphone	With wire	O
If T105 X 8 pcs	\	O
If with speedometer	\	S
Speaker for Radio and Tape Player	2 pcs	S
Lighting System	2 headlights, 2 front turn signals, 2 rear turn signals and 2 rear brake lights	S
Horn and Reverse Alarm	\	S
DC/DC Convertor	48V-12V	S
Training Gear	Gear and rack	S
Brake System	Rear and front drum hydraulic brake system	S
Accelerator	Stepless speed change	S
Front End and Front Suspension	Independent suspension	S

Rear End	With primary speed reducer and speed-change gear box	S
Rear Suspension	Steel plate suspension	S
Driving Mode	Rear wheel driving	S
Tire	20.5x8.0-10	S
Aluminum wheel	\	O
Enclosure	\	O
Solar	\	O
ACCESSORIES		
Charger	China origin, input 110V-240V~50Hz-60Hz, output 48V, 25A	S