

# Kudo

## Model 6083-X8



Cruise Car, Inc.  
P: 941.929.1630  
www.cruisecarinc.com

Descriptions:	Personal Carrier (Passenger Car)
<b>GENERAL SPECIFICATIONS</b>	
Passenger Capacity	8
Range (loaded)	49 miles
Max. Speed (m/h)	21.75
Minimum turning radius (ft)	14.75
Overall Dimensions (LxWxH) (ft)	12.83 x 4.89 x 6.36
Max. Climbing Ability (loaded)	20%
Max. Loading Weight (lbs)	1278 lbs
Net Weight (lbs)	2403 lbs
Qty/40'	3 units



<b>CONFIGURATIONS</b> ("S" stands for Standard Configuration and "O" stands for Optional Configuration)		
DESCRIPTIONS:	REMARKS:	
Body	Steel framework + fiberglass	S
Roof	Fiberglass + ABS, with hand holder	S
Windshield	Toughened glass	S
Seats: 1) Backrest and Cushion 2) Armrest	Sponge + artificial leather Stainless steel	S S
Floor	Bamboo board+ Non-slipping plastic	S
Side rear view mirror	one piece each side \$6.00 each	O
Overshadowing Curtain	\	O
Windscreen wiper	\	S
Battery	Chinese battery, 6V X 8 pcs Trojan battery T605	S O
Motor	5.5 hp	S
Controller	Curtis brand, made in USA	S
Lights	Front: 2 Headlights, 2 front turn signals, 2 side turn signals, 2 fog lights Back: 2 rear turn signals, 2 brake lights, 1 fog light	S
Dashboard	Voltmeter, ammeter, speedometer (\$30), turn signal indicator, headlight indicator, emergency switch, fog light switch; headlight switch, turn signal switch, wiper switch, horn button; Radio receiver and tape player (\$128)	S
Horn and reverse alarm	\	S
Cup drinker holder	1 pc	S
Speaker	4 pcs fixed on roof	S
Steering system	Rack and pinion steering system	S
Brake system	Front and rear drum pneumatic brake system	S
Front end and Suspension system	Independent suspension, cylinder pneumatic vibration absorber	S
Rear end and suspension system	Integrated rear end, steel plate spring suspension, cylinder pneumatic vibration absorber	S
Transmission system	Clutch, 4F+1R gear box, transmission shaft	S
Tire	145/70-R12	S
<b>ACCESSORIES</b>		
Charger	China origin, input 110V~230V, 50Hz/60Hz, output 36V, 25A, 5m DC cable, 2.5m AC cable	S