

# Kudo

## Model 6113K-X11



Cruise Car, Inc.  
P: 941.929.1630  
www.cruiseinc.com

Descriptions:	Personal Carrier (Passenger Car)		
<b>GENERAL SPECIFICATIONS</b>	<b>6113K</b>	<b>6113K01</b>	<b>6113K02</b>
Voltage	72V	48V	48V
Battery	T105 X 12 pcs	T105 X 16 pcs	T105 X 16 pcs
Motor (hp)	7.0		
Controller	Curtis 1209	Curtis 1205	Curtis 1244
Passenger Capacity	11		
Power/Voltage	5KW/72V	5KW/48V	5KW/48V
Range (loaded) (miles)	49.71	62.14	62.14
Max. Speed (m/h)	27.96	24.85	24.85
Minimum turning radius (ft)	18.04		
Overall Dimensions (LxWxH) (ft)	15.19 x 4.89 x 6.36		
Max. Climbing Ability (loaded)	20%		
Max. Loading Weight (lbs)	1609.37 lbs		
Tare weight	2645.55 lbs		
Qty/40'	2 units		
Qty/40'HQ	3 units (SKD)		



<b>CONFIGURATIONS</b> ("S" stands for Standard Configuration and "O" stands for Optional Configuration)		
DESCRIPTIONS:	REMARKS:	
Body	Steel framework + Fiberglass	S
Roof	Fiberglass + ABS, with hand holder	S
Windscreen	Toughened glass	S
Seats: 1) Backrest and Cushion	Sponge + artificial leather	S
2) Armrest	Stainless steel	S
Floor	Bamboo board+ Non-slipping plastic	S
Side rear view mirror	One piece each side	S
Inner rear view mirror	One piece each cart	O
Overshadowing curtain	Chinese	O
Windscreen wiper	\	S
DC-DC Converter	\	S
Lights	Front: 2 Headlights, 2 front turn signals, 2 side turn signals; Back: 2 rear turn signals, 2 brake lights, 1 fog light	S
Dahboard	Voltmeter, ammeter, speedometer, turn signal indicator, headlight indicator, emergency switch, fog light switch; Headlight switch, turn signal switch, wiper switch, horn button; Radio receiver and tape player	S
If with CD Player	Replacing original Radio & Tape player	O
Mircophone	Wired	O
Horn and reverse alarm	\	S
Cup drinker holder	1 pc	S
Speaker	4 pcs fixed on roof	S
Steering system	Rack and pinion steering system	S
Brake system	Front and rear drum hydraulic brake system	S
Front end and Suspension system	Independent suspension, cylinder hydraulic vibration absorber	S
Rear end and suspension system	Integrated rear end, steel plate spring suspension, cylinder hydraulic vibration absorber	S
Transmission system	Clutch, 4F+1R gear box, transmission shaft	S
Seat belt	2 point seat belt	O
Tire	145/80-R12	S
Wheel	4J*12 Steel wheel, wheel cap	S
	4J*12 Aluminum wheel	O
Enclosure	Plastic	O
<b>ACCESSORIES</b>		
Charger	China origin, input 110V~230V, 50Hz/60Hz, output 48V 72V, 25A, 5m DC cable, 2.5m AC cable	S